

## ABRR004 ROUND ROCKER SWITCH

## SWITCHES

### Specifications

### ABRR004

|                               |                                             |      |      |
|-------------------------------|---------------------------------------------|------|------|
| Rating                        | 6(2)A 250VAC T85 1E4 VDE 10A 125VAC UL C-UL |      |      |
| Colour                        | Black body/01 engraving                     |      |      |
| Switch action                 | DP On-off latching                          |      |      |
| Maximum contact resistance    | 30M $\Omega$                                |      |      |
| Minimum insulation resistance | 500VDC 100M $\Omega$                        |      |      |
| Electrical life               | 10,000 cycles                               |      |      |
| Operation force               | 600-900gf                                   |      |      |
| Operating temperature         | -25°C~85°C                                  |      |      |
| Cut out                       | Z                                           | Y    | X    |
| (diagram opposite)            | 0.75-1.25                                   | 20.8 | 20.3 |
|                               | 1.25-2.0                                    | 20.8 | 20.8 |
|                               | 2.0-3.0                                     | 20.8 | 21.1 |

Approval VDE, UL

Double pole versions available

### Features

- ROHS compliant
- Housing material:  
Nylon #66 UL 94V-2
- Rocker material:  
Nylon #66 UL 94V-2
- Terminal material:  
Copper alloy SN or AG plated
- Contact material:  
Ag-Cd-0 (12) alloy plated

